



SCR uTrust 2700 F with standing base

Article number: 775-0044-02

Short product description

SCR uTrust 2700 F

- USB 2.0 CCID with standing base , upgradable FW -

Product description

The uTrust 2700 F is the ideal PC-Linked USB contact smart card

reader for a huge variety of applications. Providing full

compliance with all major industry standards such as ISO/IEC

7816, USB CCID, PC/SC, and Microsoft

WHQL the uTrust 2700 F contact smart cards and PC operating

systems.

The full support and compliance to EMV 2008 and GSA FIPS 201

expand the use to very specific use applications requiring

additional security and data protection.

It represents the perfect mix between modern stylish design,

ergonomic handling and a compact foot print.

The extended card data transmission rate of up to 600kBit/s with

the support of

TA1=97 enables shortest possible transaction times for maximum

end user convenience.

The specific SmartOS is featuring an easy and complete

support of all major contact smart cards.

The end user experiences convenience, transaction time effi

ciency, security and reliability for use applications like

network

log-in, Windows authentication & Single Sign-On (SSO), banking

and cashless payment applications as well as high security use

cases for federal governments.

Technical specifications

Host Interface

- USB 2.0 CCID (USB1.1 / 3.0 compliant)
- 12 Mbps (USB 2.0 full speed)

SmartCard Interface

Supported standards

- ISO/IEC 7816 Part 1 to 4
- EMV 2008 Ver 4.2 Level 1

Supported Tag ICs

All major ISO/IEC 7816 compliant Smart Card IC support

Protocols

T=0, T=1

Interface speed

- up to 600 kBit/s (depending on card)
- TA1=97

Clock frequency

ISO/IEC 7816 compliant up to 5 MHz, Operates up to 12 MHz

Supported smart card types

5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C

Smart card detection

- Card present switch
- Automatic power on/off
- Short Circuit protection

Card size

ID-1

Contact type

Sliding Contact Socket (8 pin)

Driver& Software

PC/SC driver

PC/SC Specification Ver. 2.01.09 for

- Windows XP/Vista/7/8/10 (32&64Bit) / Windows Server 2003/2008/2012 Windows CE 6.0, 7.0
- MAC OS 10.5.x, 10.6.x, 10.7.x, 10.8.x
- Linux 2.4.x, 2.6.x (32&64Bit)

Software

- PC/SC API
- CT-API (through wrapper on top of PC/SC)
- Synchronous-API (through wrapper on top of PC/SC)
- M-Card API (through wrapper on top of PC/SC)

Operating System

Power supply

USB Bus powered

Dimension

70x63x62mm

Weight

204 g

Operating temperature range

0° to +50°C / +32 to +122 F

Storage temperature range

-20 to +60°C / -4 to +140 F

Operating humidity range

Up to 95% RH non condensing

Durability

Sliding Contacts 100.000 Card Insertions

MTBF

100.000 hours

Connector

1.5m USB Cable with USB Type A Connector

Status indicator

LED

Firmware

SmartOS

Firmware in-field upgradeable

Yes



Certifications / Compliances

Systems / Standards

EMV 2008 Ver 4. Level 1, ISO/IEC 7816, USB 2.0 Full Speed, CCID, Microsoft WHQL

Regulatory / Environmental

CE, FCC, UL94, UL60950, VCCI, ICES, ANZ, CNS, HBCI, GSAAPL, RoHS2, REACH, WEEE